

STERLING[®]

WALL SYSTEM

A VERSATILE RETAINING OR FREESTANDING WALL SYSTEM THAT
INSTALLS WITH AN EASY TO LOCATE PIN SYSTEM



BELGARD
PAVES THE WAY[™]



DEVELOPED BY
ANCHOR
DIAMOND
WALL INDUSTRY EXPERTS





STERLING[®]

WALL SYSTEM

A VERSATILE RETAINING OR FREESTANDING WALL SYSTEM THAT INSTALLS WITH AN EASY TO LOCATE PIN SYSTEM

📍 FEATURES & BENEFITS

- Build retaining walls with easy pin alignment and side view for placement visualization
- Block channels make easy pin alignment for battered or freestanding retaining walls
- Score marks for splitting block to make a two-sided freestanding wall unit
- Center score mark provides guide for splitting to make corner or column units
- Hand holds allow for easier handling during installation
- Maximum gravity retaining wall height is 4 ft*
- Retaining wall minimum inside radius, measured on the base course to the front of the units: 6 ft
- Retaining wall minimum outside radius, measured on the top course to the front of the units: 4 ft
- Maximum freestanding wall (FSW) height is 3 ft*
- Freestanding wall minimum radius 4 ft
- Maximum column height is 4 ft*
- Segmental retaining wall setback/system batter 10.6°

📦 SHAPES & SIZES

FREESTANDING WALL BLOCK



6 x 17¾ x 10

RETAINING WALL BLOCK



6 x 17¾ x 12

ANCHOR™ FIBERGLASS PINS*



5 x ½

UNIVERSAL CAP



3 x 18/12 x 13

* Not included on pallet.

🔴 AVAILABLE COLORS



CHARCOAL



CHESTNUT TAN



NEWPORT GRAY

BELGARD[®] | PAVES THE WAY

For more info, visit Belgard.com

NORTHFIELD WEST
13450 Johnson Memorial Drive
Shakopee, MN 55379
Ph: 952-351-9600

480 S. 16th Street
West Des Moines, IA 50265
Ph: 515-224-0200



© 2024 Oldcastle[®] APG, Inc. A CRH Company. All Rights Reserved.
Revised: 05/10/24 BEL24-412_NFD W