

# ECO DUBLIN<sup>®</sup>

*PERMEABLE PAVER*

THE CLASSIC LOOK OF CUT STONE IN A MULTI-PIECE COMBINED WITH PERMEABLE TECHNOLOGY TO REDUCE STORMWATER RUNOFF





# ECO DUBLIN<sup>®</sup>


## PERMEABLE PAVER

THE CLASSIC LOOK OF CUT STONE IN A MULTI-PIECE COMBINED WITH PERMEABLE TECHNOLOGY TO REDUCE STORMWATER RUNOFF

### 📌 FEATURES & BENEFITS

- Can eliminate stormwater runoff and improve water quality
- Meets the requirements of ASTM C936
- Optimal joint openings for infiltration
- Can be mechanically or manually installed
- Can be utilized to construct an ADA-compliant pavement
- Joint Width: 12 mm
- Initial Surface Infiltration Rate: >500 inches per hour (varies based on joint infill gradation)
- Surface Open Area: 7%
- Belgard permeable pavers can be used for a variety of different vehicular applications. Appropriate shape and thickness is based on project-specific conditions, including type of loading, base design, and subgrade conditions. It is recommended that you consult a Belgard Representative when specifying products for vehicular applications.

### 💧 AVAILABLE COLORS






RIO



VICTORIAN

### 📦 SHAPES & SIZES

#### 3-PIECE MODULAR | 80MM

-  3½ x 6⅞ x 3⅞
-  6⅞ x 6⅞ x 3⅞
-  10¼ x 6⅞ x 3⅞

**BELGARD<sup>®</sup>** | PAVES THE WAY

For more info, visit [Belgard.com](http://Belgard.com)

CPM  
4110 192nd St. East  
Tacoma, WA 98446  
Ph: 844-371-5138



© 2022 Oldcastle<sup>®</sup> APG, Inc., A CRH Company. All Rights Reserved.  
Revised: 12/07/22 BEL22-412\_CPM