

PORCELAIN COLLECTION

# QUARZITI 2.0

STONE FINISH | 20MM



This interpretation of natural quartz incorporates a gentle shading effect with the authentic diversity and subtle iridescence of natural elements.



**MIRAGE**  
INSPIRING BETTER LIVING




**v3**  **GLACIER\*\***  
**QR 01 NAT**



**v3**  **MOUNTAINS**  
**QR 02 NAT**



**v3**  **WATERFALL**  
**QR 03 NAT**



**v3**  **RIVER\*\***  
**QR 04 NAT**

\*Contact your Belgard® representative for availability and lead times.  
\*\*Contact your Belgard® representative for availability in 24 x 48 sizing.

Due to the natural materials in our products, colors may vary from those shown on the cut sheet. We recommend viewing actual product samples to ensure the perfect color and finish for each project.



## QUALITY FOR LIFE

Every step of our manufacturing process incorporates rigorous research, testing and quality assurance. We demand the highest quality from each of our facilities across North America. We believe in creating world class building products that stand the test of time. See our lifetime warranty at [Beldgard.com/Warranty](https://Belgard.com/Warranty)

## FEATURES & BENEFITS

- Organic quartz-like texture and appearance
- A variety of modular shapes offer ultimate design flexibility
- Incredibly high breakage loads, up to 3,000 pounds
- Modular for faster installation
- Unaffected by alkalis, acids, chemical agents, salt and other de-icing materials.
- Can be cleaned with normal household cleaners and even pressure washed with a low pressure washing device.\*
- High density and ultra-low absorption rate creates a tight surface texture and fends off surface mold, moss, dirt and other types of stains
- Unaffected by alkalis, acids, chemical agents, salt and other de-icing materials
- Structured top textures create non-slip surfaces
- Freeze thaw resistant—100% frost-free and properties remain unaltered at temperatures ranging from -51.1° to + 60° C (-60°F to +140°F)

*\* It is important that all pressure washing of your porcelain pavers be done with a low pressure washer with a maximum of 1600 psi and nothing more powerful. When pressure washing your installation, care should be taken to prevent damage to the grout (adhesive and grout installations) and some re-sanding will be necessary when power washing an installation with sand or polymeric sand joints.*



MODERATE VARIATION



LOW SOLAR HEAT ABSORPTION

## PALLET INFORMATION

	QUARZITI 2.0	SOFT/PALLET	SOFT/BOX	BOXES/PALLET	PCS/BOX	WEIGHT/BOX	WEIGHT/PALLET
18 X 36	17.64 x 35.35	234.9	8.7	27	2	81.4	2235
24 X 24	23.54 x 23.54 x ¾	232.5	7.75	30	2	72	2160
24 X 48	23.54 x 47.17 x ¾	279	7.75	35	1	74	2621

Downloadable professional resources available at [Beldgard.com/Resources](https://Beldgard.com/Resources)

## SHAPES & SIZES

18 X 36



17.64 x 35.35

24 X 24



23.54 x 23.54 x ¾

24 X 48



23.54 x 47.17 x ¾

View the product page on [Beldgard.com](https://Beldgard.com) for more information



LEARN MORE

**BELGARD**® | PAVES THE WAY™

AN OLDCASTLE® APG OUTDOOR BRAND

**WOODBURY**  
201 Park Ave  
Woodbury, NJ 08096

**PARKER FORD**  
16 Anderson Rd  
Parker Ford, PA 19457

**WRIGHTSTOWN**  
2 Farago Blvd  
Wrightstown, NJ 08640