
PORCELAIN COLLECTION

QUARZITI 2.0



This interpretation of natural quartz incorporates a gentle shading effect with the authentic diversity and subtle iridescence of natural elements.



WANTLE QR 05 NAT





PALLET INFORMATION

QUARZITI 2.0		SQFT/ Pallet	SQFT/ Box	BOXES/ PALLET	PCS/ BOX	WEIGHT/ Box	WEIGHT/ PALLET
12 X 24	11.73 x 23.54 x ¾	232.4	5.81	40	3	54.45	2178
18 X 36	17.64 x 35.35 x ¾	234.9	8.7	27	2	81.4	2198
24 X 24	23.54 x 23.54 x ³ ⁄4	232.5	7.75	30	2	72	2160
24 X 48	23.54 x 47.17 x ¾	271.25	7.75	35	1	74	2621
2-PIECE	11.73 x 23.54 x ¾ 23.54 x 35.35 x ¾	7.75	36	279	2	72	2592

Downloadable professional resources available at Belgard.com/Resources



AN OLDCASTLE[®] APG OUTDOOR BRAND

QUALITY FOR LIFE


Every step of our manufacturing process incorporates rigorous research, testing and quality assurance. We demand the highest quality from each of our facilities across North America. We believe in creating world class building products that stand the test of time. See our lifetime warranty at **Belgard.com/Warranty**

FEATURES & BENEFITS

- Authentic quartz-like texture and appearance
- A variety of modular shapes offer ultimate design flexibility
- Incredibly high breakage loads, up to 3,000 pounds
- Modular for faster installation
- Can be cleaned with normal household cleaners and even pressure washed with a low pressure washing device.*
- High density and ultra-low absorption rate creates a tight surface texture and fends off surface mold, moss, dirt and other types of stains
- Unaffected by alkalis, acids, chemical agents, salt and other de-icing materials
- Structured top textures create non-slip surfaces
- Freeze thaw resistant—100% frost-free and properties remain unaltered at temperatures ranging from -51.1° to + 60° C (-60°F to +140°F)

 It is important that all pressure washing of your porcelain pavers be done with a low pressure washer with a maximum of 1600 psi and nothing more powerful. When pressure washing your installation, care should be taken to prevent damage to the grout (adhesive and grout installations) and some re-sanding will be necessary when power washing an installation with sand or polymeric sand joints.

SHAPES & SIZES



View the product page on **Belgard.com** for more information



TAMPA 4630 Woodland Corporate Blvd. Tampa, FL 33614 Ph: 813-783-1970

© 2025 Oldcastle" APG, Inc. All Rights Reserved. BEL24-D-322250 | Coastal | Revised 01/2025